

automatic drain dosing system



BATTERY OPERATED

PRODUCT DATA SHEET

Cleardose is a durable and reliable dosing system suitable for indoor and outdoor applications that require the delivery of a single chemical at timed intervals.

INSTALLATION KIT

- · Drain pipe injector
- PVC delivery suction tubing
- Ceramic weight
- Foot filter
- · Silicone peristaltic tubing


DIMENSIONS	H 105 x W 210 x D 100
WEIGHT	0.775 kg (excl. batteries)
POWER	6VDC 4 X D Cell
FLOW RATE*	10ml/min - 100ml/min *Flow rates are approximate and subject to environmental conditions
MOTOR	DC Brushed motor (6VDC)
OPERATING MODES	20 events with duration from 5 sec to 3 min
CONTROL CIRCUITRY	Microchip Microprocessor
SQUEEZE TUBE FITTINGS	Standard: Compression fittings 6mm OD tube
MATERIAL	IP65 water resistant robust polypropolene injection moulded enclosure
APPROVALS	CE, Class 2 Product Certification, IP65 Rated
WARRANTY	1 year



- All events text easily visible on one screen
 Backlit display
 Extra tough selection buttons
- 4 Changeable peristaltic pump tube
- 5 Serviceable from front with one screw quick access

 6 1/4" compression connectors





	Cleardose unit	
•	Silicone peristaltic tubing	
)	Ceramic weight	
	Foot filter	
	LDPE tubing (3000mm)	
	Fixing pack (2 screws, 2 wall plugs)	
)	HT5 Silicone grease (for peristaltic tubing)	
)	Mounting bracket with spirit level	
)	Drain pipe injector	
)	Quick Start Guide	

PRODUCT CODE

Quick Start Guide

DESCRIPTION

ZCD-B

Cleardose Battery Operated

For further information, please call 01484 868 970 or email: support@biobax.co.uk WWW.biobax.co.uk



Unit 3a, Skelmanthorpe Technology Park Standback Way, Skelmanthorpe, Huddersfield HD8 9GA